



SEELEVEL Holding Tank Monitors

The tank monitor that works!

Precision accuracy

The SeeLevel II™ RV tank monitor provides percentage of full, accurate tank measurement readouts that are accurate within 3/8 of an inch.

Simple to install

Two wires connect to your existing system wires and function on a common bus system. Accessible tanks are easy to retrofit.

Customize to fit most tanks*

The senders are designed to be easily shortened or two can be combined to accommodate almost any holding tank shape or size.

** Will work on most plastic or poly holding tanks that contain any water-soluble products. Will not work on metal tanks.*

Reliable external sensors

Our trouble-free senders adhere externally to the tanks eliminating sewage build-up that can affect internal sensors.

Service and Warranty

Our professional and knowledgeable technicians are on-call to assist you with any problems you may encounter. This product offer a one-year limited warranty.

Privacy Statement

Garnet's tank monitoring tank systems require SeeLevel displays and sensors to operate. The communication protocol used between them is proprietary allowing us to control the accuracy and functionality of our systems ensuring our customers experience reliable operation.

Printed in Canada

CANADA

Garnet Instruments
286 Kaska Road
Sherwood Park, AB T8A 4G7

USA

Garnet US Inc.
5360 Old Granbury Road
Granbury, TX 76049

GARNET

Liquid management solutions, your way.

RVgauge.com

| 1-800-617-7384

SEELEVEL II™ 2-Tank System



Model 709-2P

- 3-way pump switch

FRESH • BLACK

This system monitors the fresh and black tanks and also battery voltage shown in percentage full on 3-digit LED display.

SEELEVEL II™ 3-Tank Systems

FRESH • GREY • BLACK

Monitor fresh, grey, black tanks, and battery voltage shown in percentage full on a 3-digit LED display. Various model configurations are available to display propane (LPG) level by connecting to tanks equipped with an existing sensor, activate your pump, engage your water heater. The 709-BTP3 includes Bluetooth® enabled capability and a programmable alarm.



Model 709

- Connects to existing LPG

Pump and/or Water Heater Switches



Model 709-P3

- 3-way pump switch



Model 709-P3W

- 3-way pump switch
- Connects to existing LPG

Bluetooth®



Model 709-BTP3

- Connects to existing LPG
- Bluetooth® 4.2 technology
- Programmable alarm



Model 709-HP3W

- 3-way pump switch
- Connects to existing LPG
- Water heater switch

SEELEVEL II™ RV-C 3-Tank Systems

These systems monitor three holding tanks and battery voltage shown in percentage full on a 3-digit LED display. They work with RVs that are equipped with RV-C Interface monitoring systems. The level is shown in percent of a full tank on an easy-to-read LED display. Will work on most plastic or poly holding tanks that contain any water-soluble products.



Model 709-RVC

- RV-C interface
- Connects to existing LPG
- Programmable alarm



Model 709-RVC NLP

- RV-C interface
- Programmable alarm



Model 709-RVC PM

- RV-C interface
- Momentary pump switch
- Programmable alarm

SEELEVEL II™ 4-Tank Systems

FRESH • GREY • BLACK • GALLEY

These systems monitor four holding tanks and battery voltage shown in percentage full on a 4-digit LED display. Some model configurations are available to monitor propane (LPG), activate your pump.



Model 709-4

- Basic 4-tank system



Model 709-4LP

- LPG connection
- Battery voltage displays by default





Model 709-4P

- 3-way pump switch

Externally mounted • No fouling • Precision accuracy

The SeeLevel™ Senders The SeeLevel Senders are used with SeeLevel Tank Monitoring systems that can monitor up to seven tanks and now has more efficient power consumption. The senders are mounted on the outside of the holding tanks and can be stacked to fit taller tanks. Depending on tank height and desired resolution, Garnet offers two different sender options. They are not compatible with metal holding tanks. They work on most plastic or polyethylene holding tanks that contain water-soluble fluids.. Metal holding tanks are incompatible with them.

<p>Systems include one standard size sender for each tank being monitored. The 710-AR is the standard sender that will fit most tank heights.</p> <p>On taller holding tanks, the 710-ES2 can be used to optimize tank size. If required, the standard senders can be swapped out. Contact us or a dealer for more information.</p>	 <p>9"</p> <p>710-AR</p>	 <p>12"</p> <p>710-ES2</p>
Description	Standard Sender	Optional Sender
Actual measurable length	3.5" - 10.5" (single) up to 19.5" (dual)	5.5" - 14" (single) up to 26" (dual)
No. of tanks measured	up to 7	up to 7
Resolution	1/4" (6 mm)	3/8" (10 mm)
Sender dimensions (not including tabs)	9" high x 2.45" wide	12" high x 2.45" wide
Operating temperature range	+32 °F to +140 °F (0 °C to +60 °C)	
Included with system	Yes	No

24-Nov-2022

Printed in Canada

CANADA
Garnet Instruments
286 Kaska Road
Sherwood Park, AB T8A 4G7

USA
Garnet US Inc.
5360 Old Granbury Road
Granbury, TX 76049

GARNET

Liquid management solutions, your way.

RVgauge.com | 1-800-617-7384