



SEELEVEL Holding Tank Monitors

The tank monitor that works!

Precision Perfected

The SeeLevel II™ RV tank monitor provides percentage of full, shown in percentage full on 3-digit LED display. Tank measurement readouts are accurate within 1/4 of an inch.

Simple to Install

Two wires connect to your existing system wires and function on a common bus system. Accessible tanks are easy to retrofit.

Customize to Fit Most Tanks *

The senders are designed to be easily shortened or two can be combined to accommodate almost any holding tank shape or size.

* Will work on most plastic or polyethylene holding tanks containing any water-soluble products. Will not work on metal tanks.

Reliable External Sensors

Our trouble-free senders adhere externally to the tanks eliminating sewage build-up that can affect internal sensors.

Service and Warranty

Our professional and knowledgeable technicians are ready to assist you with any problems you may encounter. This product offer a one-year limited warranty.

Privacy Statement

Garnet's tank monitoring tank systems require SeeLevel displays and sensors to operate. The communication protocol used between them is proprietary allowing us to control the accuracy and functionality of our systems ensuring our customers experience reliable operation.

Printed in Canada

CANADA
Garnet Instruments Ltd.
286 Kaska Road
Sherwood Park, AB T8A 4G7

USA
Garnet US Inc.
5360 Old Granbury Road
Granbury, TX 76049

GARNET

Liquid management solutions, your way.

RVgauge.com | 1-800-617-7384

2-Tank Systems

FRESH • BLACK

These systems monitor fresh and black tanks along with battery voltage. Some model configurations have a pump switch to activate the water pump.



Model 709-2

- Basic 2-tank configuration

Pump Switch



Model 709-2P

- 3-way pump switch

3-Tank Systems

FRESH • GREY • BLACK

These systems monitor fresh, grey, and black water tanks, along with battery voltage. Various model configurations also offer the ability to display propane (LPG) levels when connected to tanks with existing electrical sensors, and can activate the water pump or engage the water heater.

Basic Systems



Model 709

- Basic 3-tank configuration

Pump and/or Water Heater Switches



Model 709-P3

- 3-way water pump switch



Model 709-P3W

- 3-way pump switch
- Connects to existing LPG sensor



Model 709-3

- Connects to existing LPG sensor



Model 709-HP3W

- 3-way pump switch
- Water heater switch
- Connects to existing LPG

4 or More Tank Systems

FRESH • GREY • BLACK • GALLEY

These systems monitor four holding tanks and battery voltage. Some model configurations have a pump switch to activate the water pump.



Model 709-4

- Basic 4-tank configuration



Model 709-4P

- Pump switch

**On 4-tank models, the Grey and Galley tanks can only have one sender.*

UP TO 7 TANKS

Monitors up to seven holding tanks and displays battery voltage. With Bluetooth® connectivity, users can view tank levels on their mobile devices and set alerts when tank levels are too high or too low.



Model 709-BTP7

- 3-way pump switch
- Connects to existing LPG sensor
- Bluetooth® connectivity technology
- System comes with 3 senders with the option to purchase additional if required



Bluetooth® Connectivity

The SEELEVEL RV 2.0 App works on Android or iOS mobile devices.

RV-C Systems

These systems monitor three holding tanks, fresh, grey, black tanks and battery voltage. They are compatible with RVs equipped with RV-C protocol to communicate with MultiPlex systems.



Model 709-RVC NLP

- Basic RV-C configuration



Model 709-RVC

- RV-C interface
- Connects to existing LPG sensor






Model 709-RVC PM

- Basic RV-C interface with Momentary Pump switch

Externally mounted • No fouling • Precision accuracy

The SeeLevel™ Senders are key to the SeeLevel Tank Monitoring system, capable of monitoring up to seven tanks. Mounted externally, they eliminate common issues like sewage buildup found in internal probe sensors, enhancing reliability and reducing maintenance. These versatile sensors can be stacked for tall tanks or cut to fit various tank sizes. They come in three options, each offering different height and resolution capabilities. Designed to work with plastic/polyethylene, and fiberglass tanks.

| <p>Systems include one sender for each tank being monitored. Select from three (3) sender option sizes during purchasing. Extra senders can be purchased separately if required.</p> <p>Contact us or a dealer/distributor for more information.</p> |  <p>9"</p> |  <p>12"</p> |  <p>16"</p> |
|--|---|---|--|
| Description | 710-AR2 | 710-ES3 | 710-SS2 |
| Accuracy | +/- 5% or better, limited by resolution and tank height and shape. | | |
| Optimal tank height (On 4-tank models, the Grey and Galley tanks can only have one sender) | 3.5" - 11" (single) up to 20" (dual) | 4.5" - 14" (single) up to 26" (dual) | 7.5" - 18" (single) up to 34" (dual) |
| No. of tanks measured (model dependent) | up to 7 | up to 7 | up to 7 |
| Resolution | 0.25" (6 mm) | 0.33" (8 mm) | 0.44" (11 mm) |
| Sender dimensions (not including tabs) | 9" high x 2.20" wide | 12" high x 2.20" wide | 16" high x 2" wide |
| Operating temperature range | +32 °F to +140 °F (0 °C to +60 °C) | | |

Tired of unreliable tank monitors that often fall short? Experience the SeeLevel advantage and say goodbye to unreliable measurements. Ready to upgrade? Take the next step and revolutionize your tank monitoring experience with confidence.

12-Dec-2024

Printed in Canada

CANADA
Garnet Instruments Ltd.
286 Kaska Road
Sherwood Park, AB T8A 4G7

USA
Garnet US Inc.
5360 Old Granbury Road
Granbury, TX 76049

GARNET

Liquid management solutions, your way.

RVgauge.com | 1-800-617-7384